

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



EUROPEAN PATENT APPLICATION

Application number: 88302226.1

Int. Cl. 4: G02F 1/133

Date of filing: 14.03.88

Priority: 14.03.87 JP 59183/87

Date of publication of application:  
21.09.88 Bulletin 88/38

Designated Contracting States:  
DE GB


Applicant: SHARP KABUSHIKI KAISHA  
23-22 Nagaike-cho Abeno-ku  
Osaka 545(JP)

Inventor: Taniguchi, Kouki  
6-29 Nakano-cho 3-chome  
Miyakoima-ku Osaka-shi(JP)

Representative: Brown, Kenneth Richard et al  
R.G.C. Jenkins & Co. 28 Caxton Street  
London SW1H 0RJ(GB)

Liquid crystal display device.

A liquid crystal display device comprising a display screen and liquid crystal element-driving circuits. The display screen comprises an effective display region with a plurality of transparent electrodes arranged on both sides of liquid crystal elements to make characters visible and a non-display region other than the effective display region. The driving circuits are divided into two groups: the one for driving the liquid crystal elements in the effective display region to display desired characters, and the other for driving the liquid crystal elements in the non-display region to make the non-display region dark or bright.



## Liquid Crystal Display Device

### Background of the Invention

The present invention relates to a liquid crystal display device.

The conventional liquid crystal display device has a display screen comprising liquid crystal elements arranged on a plane and a pair of front and back substrates sandwiching the liquid crystal elements. On each of the front and back substrates are placed on orientational film having a rubbing layer of a predetermined direction, a transparent insulating substrate with a plurality of transparent electrodes arranged in lines thereon, and a polarizing plate with polarized light absorbing axis oriented in the predetermined direction, in this order. The front and back substrates are faced to each other with the liquid crystal elements therebetween so that the orientational films are kept in contact with the front and back sides, respectively, of the liquid crystal elements. Generally, the lines of the transparent electrodes on the front substrate intersect the lines of the transparent electrodes on the back substrate, forming a lattice. Consequently, the display screen comprises an effective display region containing picture elements in the same quantity as the intersections  $M \times N$  ( $M, N$  = the number of transparent electrode lines) between the transparent electrode lines, and a region other than the effective display region or so-called non-display region where transparent electrodes exist on either the front or the back substrate. Normally, the effective display region is framed by the non-display region on the display screen.

The orientational films and the polarizing plates are placed on both sides of the liquid crystal elements in such a manner that the rubbing layer on one side has its rubbing direction at a predetermined angle from that of the rubbing layer on the other side and that the polarized light absorbing axis of the polarizing plate on one side is directed at a predetermined angle from the direction of the polarized light absorbing axis of the polarizing plate on the other side. These angles determine the display type of the screen, that is, normally black type (or normally dark type) in which the screen transmits light when voltage is being applied between the electrodes and shuts off light when voltage is not applied, or normally white type (or normally bright type) in which the screen transmits light when voltage is not applied between the electrodes and shuts off light when voltage is being applied. Either type of the screen is employed in the conventional liquid crystal display device.

In the display screen of the above liquid crystal

display device, electrodes exist only on either side of the liquid crystal elements in the non-display region, so that driving voltage is not applied to the electrodes in the non-display region. Accordingly, when the display device is in the active state, the non-display region is either black or white depending upon the screen type. Specifically, on a normally black type screen, the non-display region is distinguished as a black frame, whereas on a normally white type screen, the non-display region is not distinguishable from the effective display region.

Therefore, when characters are displayed on the normally black type screen, a part of the characters may combine with the black non-display region, resulting in an illegible display of characters. When characters are to be displayed on the normally white type screen, on the other hand, it is difficult for the operator to plan the layout because of the undistinguishability of the effective display region from the non-display region; the operator is obliged to input characters without clear knowledge of the boundary of the effective region. Against this background, a liquid crystal display device whose non-display region can be made dark or bright as desired depending upon the state on the effective display region has been demanded but not yet realized.

### Summary of the Invention

In view of the above conventional problems, an object of the present invention is to provide a liquid crystal display device having a display screen comprising an effective display region for showing characters and a region which surrounds the effective display region and is capable of changing the display state depending upon the display state on the effective display region.

Another object of the present invention is to provide a liquid crystal display device whose display screen is divided into an effective display region for showing characters and a non-display region where no characters are displayed, the effective display region being defined by the non-display region.

Further object of the present invention is to provide a liquid crystal display device capable of displaying a non-display region on the display screen selectably in black or in white.

Other objects and further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. It should be understood, however, that the detailed descrip-

tion and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

To achieve the above objects, according to an embodiment of the present invention, a liquid crystal display device contains a display screen comprising an effective display region in which a plurality of transparent electrodes are arranged in lines on both sides of liquid crystal elements so as to display characters and a region other than said effective display region or a non-display region where characters are not displayed; and liquid crystal driving means comprising circuits for driving the liquid crystal elements arranged in said effective display region to display desired characters, and circuits for driving the liquid crystal elements arranged in said non-display region so as to make the non-display region either dark or bright as desired.

As described above, the liquid crystal display device of the present invention contains the display screen comprising the effective display region and the non-display region, and drives the liquid crystal elements in the non-display region independently of those in the effective display region, so that the non-display region can be made bright or dark as desired.

Since it is possible to select dark or bright state for the non-display region according to the display state in the effective display region, the effective display region is distinguishable from the non-display region.

### Brief Description of the Drawings

The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention and wherein: Fig. 1 is a block diagram showing the electrical construction of the liquid crystal display device of an embodiment of the present invention;

Fig. 2 is a block diagram of one of the circuits for driving the horizontal transparent electrode lines of an embodiment of the present invention; Fig. 3 is a block diagram of one of the circuits for driving the vertical transparent electrode lines of the embodiment of the present invention; and Fig. 4 is a construction drawing of the liquid crystal display device of the present invention.

### Detailed Description of the Embodiment

Fig. 4 shows the construction of the liquid crystal display device of an embodiment of the present invention.

Referring to the Figure, a front transparent substrate 2 and a back transparent substrate 2' are mounted each on both sides of liquid crystal elements 6 via sealing members 7. An orientational film 5 or 5' having a rubber layer of a predetermined direction, plural lines of transparent electrodes 4 or 4' and an insulating film 3 or 3' are provided on each of the front and back transparent substrates 2 and 2' on the side facing the liquid crystal elements 6. A polarizing plate 1 or 1' whose polarized light absorbing axis is oriented in a specified direction is provided on the other side of each of the front and back substrates 2 and 2'. The transparent electrodes 4 and 4' are arranged on the front and back substrates 2 and 2' so that they intersect each other to form a lattice with the liquid crystal elements 6 therebetween. Therefore, an effective display region comprising picture elements of the same quantity as the intersections  $M \times N$  ( $M$ ,  $N$  = the number of transparent electrode lines) between the transparent electrodes 4 on the front substrate 2 and the transparent electrodes 4' on the back substrate 2' and a display region containing either of the transparent electrodes 4 and 4' or so-called a non-display region where no characters are displayed are formed in the display screen. On the display screen, the effective display region is surrounded by the non-display region.

In the following description of the liquid crystal display device of the present invention, it is assumed the number of transparent electrodes  $M$  on one side is 200, that the number of transparent electrodes  $N$  on the other side is 840, and that the number of picture elements in the effective display region is  $200 \times 840 = 128,000$ .

Fig. 1 is a block diagram showing the electrical construction of the liquid crystal display device 11 of the present invention. A display screen 11a comprises an effective display region A where characters and figures are visibly displayed and regions other than the effective display region or non-display regions B1, B2, ..., B8 (The entire non-display regions are hereinafter referred to by B.) where no characters and figures are displayed. The effective display region A contains plural lines of horizontal transparent electrodes 12a1, 12a2, ..., 12aY, 12b1, 12b2, ..., 12bY (The entire horizontal transparent electrodes are hereinafter referred to with 12. In the present embodiment,  $Y = 100$  so that the total number of the horizontal electrodes is 200.) and plural lines of vertical transparent electrodes 13a1, 13a2, ..., 13aX, 13b1, 13b2, ..., 13bX (The entire vertical transparent electrodes are

hereinafter referred to by 13. In the present embodiment,  $X = 640$  so that the total number of the vertical electrodes is 1,280, divided into an upper and lower groups and intersecting the horizontal transparent electrodes 12 to form a lattice. Accordingly,  $(2X) \times (2Y)$  (or  $2 \times 640 \times 2 \times 100 = 256,000$  in the present invention) intersections are formed between the horizontal transparent electrodes 12 and the vertical transparent electrodes 13, and picture elements "p" of the same number as the intersections are formed in the effective display region A.

The non-display region B surrounding the effective display region A comprises six non-display regions B1 through B6 realized by at least two horizontal transparent electrodes 14a and 14b (represented by 14) and at least four vertical transparent electrodes 15a, 15b, 15c and 15d (represented by 15) divided vertically into two groups. The horizontal transparent electrodes 14 intersect the vertical transparent electrodes 13 and 15. The vertical transparent electrodes 15 intersect the horizontal transparent electrodes 12 and 14. In the Fig. 1, the non-display region B is distinguished by oblique lines.

Driving voltages suitable to the display state of and a desired character pattern on the display screen 11a are applied sequentially at a predetermined timing to the horizontal transparent electrodes 12 and 14 and to the vertical transparent electrodes 13 and 15 from driving means comprising a plurality of driving circuits which are later described.

Driving circuits YD1 and YD2 (The two driving circuits are hereinafter referred to by YD.) supplying driving voltage to the plurality of the horizontal transparent electrodes 12 have 102 output terminals each. The total 204 output terminals are allotted with the serial reference numbers yd0 through yd101 and yd102 through yd203. (The entire output terminals are hereinafter referred to by yd. The output terminals yd101 and yd102 are not connected to the horizontal transparent electrodes 12.) The lines connected to the output terminals yd are allotted with the serial reference numbers 1yd0 through 1yd201 (represented by 1yd).

The first output terminal yd0 and the last output terminal yd203 of the driving circuits YD are connected through the lines 1yd0 and 1yd201 to the horizontal transparent electrodes 14a and 14b of the non-display regions B1 and B2, respectively. All the other output terminals yd1 through yd202 (excluding the terminals yd1 and yd102) are connected via the lines 1yd1 through 1yd200 to the horizontal transparent electrodes 12 one to one.

Driving circuits XD1, XD2, ..., XD2n ( $2n = 16$  in this embodiment. The entire driving circuits are hereinafter referred to by XD) supplying driving

voltage to the plurality of the vertical transparent electrodes 13 have, say, 82 output terminals each. The total 1,312 output terminals are allotted with the serial reference numbers xd0 through xd1312. (The entire output terminals are hereinafter referred to by xd. The last output terminal xd81 of the driving circuit XD1, the first and the last output terminals xd82, xd163, xd164, xd245, xd246, xd327, ..., xd1148 and xd1229 of the subsequent driving circuits XD2 through XD15 and the first output terminal xd1230 of the driving circuit XD16 are not connected to the vertical transparent electrodes 13.) The lines connected to the output terminals xd are allotted with the serial reference numbers 1xd0 through 1xd1289 (represented by 1xd).

The first output terminal xd0 of the driving circuit XD1 and the last output terminal xd655 of the driving circuit XDn are connected through the lines 1xd642 and 1xd1283 to the vertical transparent electrodes 15c and 15d of the non-display regions B5 and B6, respectively. All the other output terminals xd1 through xd1310 (excluding the terminals xd82, xd163, xd164, xd245, xd246, xd327, ..., xd1148, xd1229 and xd1230) are connected via the lines 1xd1 through 1xd1282 to the vertical transparent electrodes 13 one to one.

In the display device 11 of the above construction, driving voltages are output through the output terminals yd and xd of the driving circuits YD and XD at predetermined timings in the sequences corresponding to the desired display pattern so as to scan the display screen 11a, whereby each picture element p transmits or shuts off light, that is, becomes bright or dark when driving voltage is being applied. Specifically, for a normally black (or normally dark) type of display screen, the picture element p transmits light when driving voltage is applied between the electrodes, and shut off light when driving voltage is not applied, whereas for a normally white (or normally bright) type of display screen the picture elements p transmit light when driving voltage is not applied and shut off light when driving voltage is applied.

When the display screen 11a is irradiated from the back side by a light source (not shown) positioned in the rear side of perpendicularly to the paper showing Fig. 1, the desired characters or figures displayed on the screen 11a can be seen from the front side of the screen 11a. While the screen 11a is being scanned, if voltage outputs from the driving circuits XD1 through XD8 are shut off in the timing of applying voltage to the horizontal electrode 14a of the non-display region B1, namely, during the period when voltage is supplied through the output terminal yd0 of the driving circuit YD1, no voltage is applied to the horizontal transparent electrode 14a. As a result, when the display screen 11a is of the normally black type,

the non-display region B1 becomes dark and distinguished as a black frame. When the display screen 11a is of the normally white type, on the other hand, the non-display region B1 becomes bright so that the black frame disappears. If outputs from the driving circuits XD1 through XD8 are connected to the vertical electrodes during the above mentioned period, voltage is applied to the horizontal transparent electrode 14a. Consequently, when the display screen 11a is of the normally black type, the non-display region B1 becomes bright so that the black frame disappears, and when the display screen 11a is of the normally white type, the non-display region B1 becomes dark, being distinguished as a black frame. All the other non-display regions B2 through B6 operate similarly as the non-display region B1.

As understood from the above, the liquid crystal display device of the present invention is characterized in that a plurality of horizontal transparent electrodes 14 and a plurality of vertical transparent electrodes 15 are provided even in the non-display region B of the display screen 11a, permitting voltage from the driving circuits YD and XD to be applied between the transparent electrodes 14 and 15 in the non-display region B at a predetermined timing independent of the voltage application to the transparent electrodes in the effective non-display region B.

Fig. 2 is a block diagram showing the construction of one driving circuit YD which supplies driving voltage to the horizontal transparent electrodes of the display device of the present invention, and Fig. 3 is another block diagram showing the construction of one driving circuit XD for supplying driving voltage to the vertical transparent electrodes.

Referring to Fig. 2, the driving circuit YD is activated by application of supply voltage  $V_{DD}$  and  $V_{SS}$ . The driving circuit YD is provided with, say, 102 output terminals yd0 through yd101 (represented by yd).

According to the present embodiment, the driving circuits YD comprises two driving circuits YD1 and YD2. The output terminal yd0 of the driving circuit YD1 and the output terminal yd203 of the driving circuit YD2 are connected to the horizontal transparent electrode 14a of the non-display region B1 and to the horizontal transparent electrode 14b of the non-display region B2, respectively. The output terminal yd101 of the driving circuit YD1 and the output terminal yd102 of the driving circuit YD2 are not connected to the horizontal electrodes. The output terminals yd1 through yd100 of the driving circuit YD1 are connected to the horizontal transparent electrodes 12a1 through 12aY, and the output terminals yd103 through yd202 of the driving circuit YD2 to the horizontal transparent elec-

trodes 12b1 through 12bY. The operation of the driving circuits YD is described below focusing on the driving circuit YD1. The driving circuit YD2 operates similarly as the driving circuit YD1.

Driving voltage of four levels in accordance with the density of characters to be displayed on the screen is supplied from a driver Ya via line L0 through L101 to the output terminals yd (yd0 through yd101). The level of the driving voltage is determined by a level signal selected by the driver Ya from among four kinds of level signals supplied through level terminals vy1 through vy4 to the driver Ya while a level alternating signal supplied through a level selecting terminal dly from a control circuit (not shown) is input to the driver Ya via a level shifter Yb and a line L201.

Data signals are input through a data input terminal dya to a shift register Yc which outputs the data signals sequentially in shift through a line L202, for scanning or selectively driving 101 horizontally transparent electrodes (including those for the non-display region) through the output terminals yd0 through yd100. During the scanning period, driving voltage is or is not applied to the last output terminal yd101 and the first output terminal yd0 for the non-display region, depending upon the display state of the screen. Supposing driving voltage is being applied to the vertical transparent electrodes and that the display screen 11a is of normally black type, the non-display region becomes bright when driving voltage is supplied to the output terminals yd0 and yd101, and becomes dark when driving voltage is not supplied. On the display screen 11a of normally white type, the non-display region becomes dark when driving voltage is supplied to the output terminals yd0 and yd101, and becomes bright when it is not supplied. When driving voltage is not applied to the vertical transparent electrodes, the non-display region is dark on the normally black type screen and bright on the normally white type screen regardless of whether or not driving voltage is supplied to the output terminals yd0 and yd101.

Referring to Fig. 3, each driving circuit XD is activated by application of supply voltages  $V_{DD}$  and  $V_{SS}$ . Each driving circuit XD is provided with, say, 82 output terminals xd0 through xd81 (represented by xd).

According to the present embodiment, the driving circuits XD comprises the driving circuits XD1 through XD<sub>2n-18</sub>. Of the 82 output terminals of each of the driving circuits XD, the output terminal xd0 of the driving circuit XD1, the output terminal xd855 of the driving circuit XD<sub>n-8</sub>, the output terminal xd856 of the driving circuit XD9 and the output terminal xd1312 of the driving circuit XD<sub>2n-18</sub> are connected to the vertical transparent electrodes 15a, 15b, 15c and 15d of the non-display regions

B3, B4, B5 and B6, respectively. The last output display xd81 of the driving circuit XD1 and the last output terminal xd737 of the driving circuit XD8 are not connected to the vertical transparent electrodes. The first output terminal xd573 of the driving circuit XD<sub>0=8</sub> and the first output terminal xd1230 of the driving circuit XD<sub>20=16</sub> are not connected to the vertical transparent electrodes. In short, the first and the last of the 82 output terminals of each of the driving circuits XD are either connected to the vertical transparent electrodes 15a through 15d of the non-display region B or not connected to any electrodes. All the remaining output terminals are connected to the vertical transparent electrodes in the effective display region one to one.

The operation of the driving circuits XD is described below focusing on the driving circuit XD1. The other driving circuits operate similarly as the driving circuit XD1.

The output terminals xd1 through xd80 of the driving circuit XD are connected one to one to the vertical transparent electrodes 13 of the effective display region A. Driving voltage of four levels in accordance with the density of characters to be displayed on the screen is supplied to the output terminals xd (xd0 through xd81) from a driver Xa via lines m0 through m81. The level of the driving voltage is determined by a level signal selected by the driver Xa from among four kinds of level signals supplied to the driver Xa through level terminals vx1 through vx4 while a level alternating signal supplied through a level selecting terminal dfx from a control circuit (not shown) is input to the driver Xa via a level shifter Xb and a line m201.

Selecting data signals are input through four data input terminals dxa, dxb, dxc and dxd to a shift register Xd which outputs the signals sequentially in shift to a latch circuit Xc via a line m203, for scanning or selectively driving 80 vertical transparent electrodes 13 (excluding the one for the non-display region) through the output terminals xd1 through xd80. Meanwhile, a non-display selecting data signal supplied via a non-display selecting terminal fr is input to the latch circuit Xc through lines m301 and m304 according to the display state on the screen. Supposing driving voltage is being applied to the non-display region B1 or B2 (through the output terminal yd0 or yd203 in Fig. 2) by the horizontal transparent electrode-driving circuit YD, when a load signal is input to the latch circuit Xc via a load signal terminal load, the latch circuit Xc latches the non-display selecting data signal. Thus, the signal instructing the display of the non-display region B is transmitted through a line m202 to the level shifter Xb to the line m201 to the driver Xa, whereby driving voltage is output to all of the output terminals xd1 through xd80 or not

output to any of them depending upon the display type (normally black or normally white) of the display screen 11a.

Meanwhile, driving voltage is output through a line m302 or m305 to the level shifter Xb to a line m303 or m308 to the output terminal xd0 or xd81 connected to the vertical transparent electrode 15 of the non-display region. The driving voltage may be output or may not be output depending upon the display type (normally black or normally white) of the display screen 11a.

According to the present invention, as understood from the above, driving voltage output is connected to or shut off from the electrodes in the non-display region independent of the voltage application to the effective display region for character display, whereby a black frame can be shown on the non-display region of the display screen as desired. As a result, the display performance of the liquid crystal display device is remarkably improved.

In the above embodiment, the display device provides monochromatic pictures. It is possible to provide a color pictures when a color filter corresponding to the picture elements is placed on either of the two orientational films constituting the display screen. The number of picture elements in the effective display region of the display screen is  $2 \times 840 \times 200 = 256,000$  in the present invention, although it is not limited to this figure. Further, in the present embodiment, some of the output terminals of the driving circuits which form driving means remains unconnected to transparent electrodes. The driving circuits may have such a construction that all the output terminals of the driving circuits are connected to the electrodes in the effective display region. The number of required driving circuits may be decreased depending upon the number of the picture elements.

As described in the above, the liquid crystal display device of the present invention contains both horizontal and vertical transparent electrodes even in the non-display region other than the effective display region of the display screen, and display means for driving each transparent electrode arranged in the non-display region independent of the other electrodes in the effective display region, so that the non-display region can be made dark or bright as desired. Namely, it is possible to show or erase a black frame on the non-display region of the screen depending upon the display state on the screen. Consequently, the use and display performance of the liquid crystal display device are improved remarkably.

While only certain embodiments of the present invention have been described, it will be apparent to those skilled in the art that various changes and modifications may be made therein without depart-

ing from the spirit and scope of the present invention as claimed.

There are described above novel features which the skilled man will appreciate give rise to advantages. These are each independent aspects of the invention to be covered by the present application, irrespective of whether or not they are included within the scope of the following claims.

#### Claims

1. A liquid crystal display device, comprising: a display section comprising an effective display region with a plurality of transparent electrodes arranged on both sides of liquid crystal elements so as to make characters visible, and a non-display region other than said effective display region; and liquid crystal driving means comprising first driving circuits for driving the liquid crystal elements in said effective display region to display desired characters, and second driving circuits for driving the liquid crystal elements in said non-display region to make said non-display region dark or bright.

2. The liquid crystal display device of claim 1, wherein said display section is of either normally black type or normally white type selectable as desired.

3. The liquid crystal display device of claim 2, wherein when said display section is of normally black type, said non-display region is driven to become bright by said second driving circuits of the liquid crystal driving means.

4. The liquid crystal display device of claim 2, wherein when said display section is of normally white type, said non-display region is driven to become dark by said second driving circuits.


5. The liquid crystal display device of claim 1, wherein said non-display region defines said effective display region.

6. A liquid crystal display device which is operable for pattern display within a display region of a display area, the display area also including a non-display region adjacent said display region, characterised in that the device includes control means which is selectively operable to change the display brightness of said non-display region.

7. A liquid crystal display device according to claim 6 characterised in that said control means is operable to change said display brightness of said non-display region relative to that of character display in said display region.



Neu eingereicht / Newly filed  
Nouvellement déposé



Neu eingeleitet / Newly filed  
Patent application

FIG. 2.




FIG. 3.





FIG. 4.



ATTACHMENT D

1. European Patent Application Number GB 2 214 342 A.